



<p>125' Straight Rough Terrain Boom Lifts</p>	
<p>Click Picture To Enlarge</p>	
<p>Model Number</p>	<p>S-125</p>
<p>Platform Height</p>	<p>125' 2" (38.15 m)</p>
<p>Horizontal Outreach</p>	<p>81' (24.68 m)</p>
<p>Swing</p>	<p>360 degrees continuous</p>
<p>Platform Capacity</p>	<p>500 lb (227 kg)</p>
<p>Platform Rotator</p>	<p>160 degrees</p>
<p>Jib (Range of Articulation)</p>	<p>5'</p>
<p>Platform Size</p>	<p>36" x 96" (0.91 x 2.44 m)</p>
<p>Overall Width Axles Retracted</p>	<p>8' 2" (2.49 m)</p>
<p>Overall Width Axles Extended</p>	<p>11' (3.35 m)</p>
<p>Stowed Height</p>	<p>10' 1" (3.07 m)</p>
<p>Stowed Length</p>	<p>46' 9" (14.25 m)</p>
<p>Wheelbase</p>	<p>12' (3.66 m)</p>
<p>Ground Clearance</p>	<p>1'5.5" (0.44 m)</p>
<p>Gross Vehicle Weight</p>	<p>44, 640 lb (20,248 kg)</p>
<p>Drive Speed</p>	<p>3.0 mph (4.8 kmph)</p>
<p>Turning Radius Inside Axles Retracted</p>	<p>27' 2" (8.28 m)</p>
<p>Turning Radius Inside Axles Extended</p>	<p>18' (5.49 m)</p>
<p>Turning Radius Outside Axel Retracted</p>	<p>43' 1" (13.13 m)</p>
<p>Turning Radius Outside Axel Extended</p>	<p>39' 7" (12.06 m)</p>
<p>Tailswing</p>	<p>5' 6" (1.67 m)</p>